

Section 1: Identification

Product identifier	Husqvarna X-Guard Bio Chain Oil
Other means of identification	
Product code	596 45 73-05 (200L), 596 45 73-04 (20L), 596 45 73-03 (10L), 596 45 73-02 (5L), 596 45 73-01 (1L)
Recommended use of the chemical and restrictions on use	
Recommended use	Lubrication of saw chains.
Restrictions on use	None.
Details of manufacturer or importer	
Supplier	Husqvarna New Zealand Ltd
Address	51 Aintree Avenue, Mangere, Auckland 2022
Country	New Zealand
Telephone	+64 9 920 2410
Contact person	Colin Stimpson
E-mail	colin.stimpson@husqvarnagroup.com
Emergency	Contact the Poisons Information Centre; phone 0800 764 766

Section 2: Hazard identification

Classification of the hazardous chemical

Physical hazards	Not classified.
Health hazards	Not classified.
Environmental hazards	Not classified.

Label elements, including precautionary statements

Hazard symbol(s)	None.
Signal word	None.
Hazard statement(s)	The mixture does not meet the criteria for classification.
Precautionary statement(s)	
Prevention	Not assigned.
Response	Not assigned.
Storage	Not assigned.
Disposal	Not assigned.

Other hazards which do not result in classification None.

Supplemental information Safety data sheet available on request.

Section 3: Composition/information on ingredients

Substance or mixture	Mixture		
Chemical property		CAS Number	Concentration (%)
Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)		-	1 - 5

Section 4: First-aid measures

Description of necessary first aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.

Personal protection for first-aid responders Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

Symptoms caused by exposure Direct contact with eyes may cause temporary irritation.

Medical attention and special treatment Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Section 5: Fire-fighting measures

Extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

Extinguishing media to avoid Do not use water jet as an extinguisher, as this will spread the fire.

HAZCHEM Code Number None.

Specific hazards during fire fighting During fire, gases hazardous to health may be formed.

Special fire fighting procedures Move containers from fire area if you can do so without risk.

Protection of fire-fighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Hazards from combustion products Fumes, smoke, carbon monoxide and other products of incomplete combustion.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapour. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

For emergency responders Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

Methods and materials for containment and cleaning up The product is immiscible with water and will spread on the water surface.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Section 7: Handling and storage

Precautions for safe handling Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid breathing mist or vapour. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in original tightly closed container. Store away from incompatible materials (see section 10 of the SDS).

Section 8: Exposure controls/personal protection

Control parameters Follow standard monitoring procedures.

Occupational exposure limits No exposure limits noted for ingredient(s).

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, for example personal protective equipment (PPE)

Eye/face protection Face shield is recommended. Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

Section 9: Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Liquid.
Colour	Yellow.

Odour Characteristic. Mild.

Odour threshold Not available.

pH Not available.

Melting point/freezing point -36 °C (-32.8 °F)

Initial boiling point and boiling range Not available.

Flash point > 200.0 °C (> 392.0 °F)

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available.

Flammability limit - upper (%) Not available.

Vapour pressure Not available.

Vapour density Not available.

Relative density 0.918 (20 °C)

Solubility(ies)

Solubility (water) Insoluble in water.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Other physical and chemical parameters

Explosive properties Not explosive.

Oxidising properties Not oxidising.

Section 10: Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidising agents.

Hazardous decomposition products No hazardous decomposition products are known.

Section 11: Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Product	Species	Test Results
Husqvarna X-Guard Bio Chain Oil (CAS Mixture)		
Acute		
Dermal		
LD50		> 2000 mg/kg
Inhalation		
LC50		> 20 mg/l, 4 hours
Oral		
LD50		> 2000 mg/kg

Components	Species	Test Results
Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %) (CAS -)		
Acute		
Dermal		
LD50	Rat	> 1700 mg/kg
Inhalation		
<i>Aerosol</i>		
LC50	Rat	> 5.28 mg/l, 4 hours
Oral		
LD50	Rat	> 4150 mg/kg

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory irritation	High mist concentrations may cause irritation of respiratory tract.
Respiratory or skin sensitisation	
Respiratory sensitisation	Not a respiratory sensitiser.
Skin sensitisation	This product is not expected to cause skin sensitisation.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Not classifiable as to carcinogenicity to humans.
ACGIH Carcinogens	Not available.
IARC Monographs. Overall Evaluation of Carcinogenicity	Not listed.
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Narcotic effects	No data available.
Chronic effects	Prolonged and repeated contact with used oil may cause serious skin diseases, such as dermatitis and skin cancer.

Section 12: Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
--------------------	--

Product	Species	Test Results
Husqvarna X-Guard Bio Chain Oil (CAS Mixture)		
Aquatic		
<i>Acute</i>		
Algae	IC50	Algae > 100 mg/l
Crustacea	EC50	Daphnia > 100 mg/l
Fish	LC50	Fish > 100 mg/l

Components	Species		Test Results
Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %) (CAS -)			
Aquatic			
Crustacea	EL0	Daphnia magna	>= 1000 mg/l, 48 hours
Fish	LL0	Oncorhynchus mykiss	>= 1000 mg/l, 96 hours
Persistence and degradability	The product is expected to be biodegradable.		
Bioaccumulative potential	No data available.		
Mobility in soil	No data available.		
Other adverse effects	Oil spills are generally hazardous to the environment.		

Section 13: Disposal considerations

Disposal methods	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
Special precautions to be taken during disposal	Dispose in accordance with all applicable regulations.
Method of disposal that should not be used	None known.

Section 14: Transport information

IATA	Not regulated as dangerous goods.
IMDG	Not regulated as dangerous goods.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.

Section 15: Regulatory information

Applicable regulations	New Zealand Code of Practice for the Preparation of Safety Data Sheets (SDS) [No. HSNO CoP 8-1 09-06].
	Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, aromatics (2-30%): HSNO - Lubricants (Low Hazard) Group Standard 2006 [HSR 002605] 6.1E, 9.1D

Section 16: Other information

References	ECHA CHEM
Issued by	Not available.
Prepared by	Not available.
Disclaimer	Husqvarna AB cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.
Issue date	07-November-2018
Revision date	-