



Husqvarna 4-stroke oil 5W-30

Husqvarna 4-stroke oil 5W-30 is a high quality synthetic motor oil for use in low temperatures. The oil is perfect for Husqvarna Snow throwers. It is also suitable for use in air-cooled and water-cooled 4-stroke lawnmowers, small tractors, rotary hoes, tool carriers and other manufacturer engines according to its specifications.

Because of excellent cold temperature features, the oil succeeds to maintain its flow ability even in hard winter conditions and ensures engines optimal lubrication immediately from cold start. It protects the engine against wear and keeps it clean during the whole drain interval.

Husqvarna 4-stroke oil 5W-30 is specially developed for to protect engines which require API SN and ILSAC GF-5 standards.

PROPERTIES	TYPICAL RESULT	TEST METHOD
SAE Grade	5W-30	
Density [kg/dm ³]	0,85	ASTM D4052
Kinematic viscosity [mm ² /s]		ASTM D445
at 100° C	11,4	
at 40° C	63	
Viscosity index	177	ASTM D2270
Cold crank simulator (CCS) @ -30°C [mPa.s]	2900	ASTM D5293
Mini Rotary Viscosity (MRV) @ -35°C [mPa.s]	10200	ASTM D4684
Flash point [° C]	233	ASTM D92
Pour point [° C]	-43	ASTM D5950
Evaporation loss [wt%]	12,3	ASTM D5800
TBN [mgKOH/g]	8,5	ASTM D2896
TAN [mgKOH/g]	2,4	ASTM D664
Sulfated Ash [wt%]	0,82	ASTM D874
Shelf life [years]	3	

PNC	NAME
597686801	4T OIL 5W30 1L