Husqvarna[®]

SAFETY DATA SHEET

1. Identification

Product identifier	Husqvarna Care and Shine Spray		
Other means of identification			
Product code	593967901, 590855101, 590855102		
Recommended use	Care and clean for plastic parts on automowers.		
Recommended restrictions	Use in accordance with supplier's recommendations.		
Manufacturer/Importer/Supplier/	Distributor information		
Manufacturer/Supplier	Husqvarna Professional Products, Inc.		
Address	9335 Harris Corners Parkway,		
	Charlotte NC 28269, US		
Telephone	'+ 1 704 921 7078		
Contact person	Randy Rush		
E-mail	randy.rush@husqvarnagroup.com		
Emergency telephone number	+1-760-476-3962 (Access code 333721)		
2. Hazard identification			
Physical hazards	Not classified.		
Health hazards	Sensitization, skin	Category 1	
Label elements			
	\land		
	$\mathbf{\nabla}$		
Signal word	Warning		
Hazard statement	May cause an allergic skin reaction.		
Precautionary statement			
Prevention	Keep out of reach of children. Avoid breathing not be allowed out of the workplace. Wear prot	mist/vapours. Contaminated work clothing should tective gloves.	
Response	IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If medical advice is needed: Have product container or label at hand.		
Storage	Not assigned.		
Disposal	Dispose of contents/container in accordance w	vith local/regional/national/international regulations.	
Other hazards	None known.		
Supplemental information			
Other hazards	None known.		

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Propan-2-ol		67-63-0	1 - 5
2-Methyl-2H-isothiazol-3-one		2682-20-4	0.0015 - <0.01
Composition comments	All concentrations are in percent by weight ur percent by volume.	less ingredient is a gas. Gas	s concentrations are in
4. First-aid measures			
Inhalation	Move to fresh air. Call a physician if symptom	s develop or persist.	
Skin contact	Wash off with soap and water. Get medical at	tention if irritation develops	and persists.

Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Alcohol-resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	The product is combustible, and heating may generate vapours which may form explosive vapour/air mixtures. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Cool containers exposed to flames with water until well after the fire is out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Combustible liquid.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. Avoid contact with skin and eyes. In case of spills, beware of slippery floors and surfaces.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. This product is miscible in water.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground. Environmental manager must be informed of all major releases.
7. Handling and storage	
Precautions for safe handling	Use only in well-ventilated areas. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using the product. When using do not smoke. Keep away from open flames, hot surfaces and sources of ignition. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Туре	Value	
STEL	400 ppm	
TWA	200 ppm	
	Type STEL	Type Value STEL 400 ppm

Components	•	Туре	edule 1, Table 2) Va	lue
Propan-2-ol (CAS 67-63-0)		STEL	984	4 mg/m3
			400) ppm
		TWA	492	2 mg/m3
			20) ppm
Canada. British Columbia Safety Regulation 296/97, a		ational Exposure Limits	for Chemical Su	bstances, Occupational Health and
Components		Туре	Va	lue
Propan-2-ol (CAS 67-63-0)		STEL	400) ppm
		TWA	20) ppm
Canada. Manitoba OELs (F Components	Reg. 217/2006,	The Workplace Safety A Type	-	lue
		STEL	40	maga C
		TWA) ppm
				- Fb
Canada. Ontario OELs. (Co Components	ontrol of Expo	sure to Biological or Cho Type		lue
Propan-2-ol (CAS 67-63-0)		STEL	40) ppm
		TWA	20) ppm
Canada. Quebec OELs. (M Components	inistry of Labo	or - Regulation respectin Type		ealth and safety) lue
Propan-2-ol (CAS 67-63-0)		STEL	123	30 mg/m3
1000000000000000000000000000000000000				
			50) ppm
		TWA		·
		TWA	983) ppm
Canada. Saskatchewan OE	ELs (Occupatio		983 400 egulations, 1996) ppm 3 mg/m3) ppm
Canada. Saskatchewan OE Components Propan-2-ol (CAS 67-63-0)	ELs (Occupatio	onal Health and Safety R	98: 400 egulations, 1996 Va	D ppm 3 mg/m3 D ppm , Table 21)
Canada. Saskatchewan OE Components	ELs (Occupatio	onal Health and Safety R Type	98: 400 egulations, 1996 Va 400	0 ppm 3 mg/m3 0 ppm , Table 21) Iue
Canada. Saskatchewan OE Components Propan-2-ol (CAS 67-63-0)	ELs (Occupatio	onal Health and Safety R Type 15 minute	98: 400 egulations, 1996 Va 400	0 ppm 3 mg/m3 0 ppm , Table 21) lue
Canada. Saskatchewan OE Components Propan-2-ol (CAS 67-63-0) Ogical limit values		onal Health and Safety R Type 15 minute	98: 400 egulations, 1996 Va 400	0 ppm 3 mg/m3 0 ppm , Table 21) Iue
Canada. Saskatchewan OE Components Propan-2-ol (CAS 67-63-0) ogical limit values ACGIH Biological Exposur		onal Health and Safety R Type 15 minute	98: 400 egulations, 1996 Va 400	0 ppm 3 mg/m3 0 ppm , Table 21) Iue
Canada. Saskatchewan OE Components Propan-2-ol (CAS 67-63-0) ogical limit values ACGIH Biological Exposur Components	e Indices Value	onal Health and Safety R Type 15 minute 8 hour	98: 400 egulations, 1996 Va 400 200	D ppm 3 mg/m3 D ppm , Table 21) lue D ppm D ppm
Canada. Saskatchewan OE Components Propan-2-ol (CAS 67-63-0) ogical limit values ACGIH Biological Exposur Components Propan-2-ol (CAS 67-63-0)	re Indices Value 40 mg/l	onal Health and Safety R Type 15 minute 8 hour Determinant Acetone	98: 400 egulations, 1996 Va 400 200 Specimen	D ppm 3 mg/m3 D ppm , Table 21) lue D ppm D ppm
Canada. Saskatchewan OE Components Propan-2-ol (CAS 67-63-0) ogical limit values ACGIH Biological Exposur	Te Indices Value 40 mg/l ase see the sou Good gene applicable, maintain air	Determinant Acetone Trce document. Tal ventilation should be us use process enclosures, labeled and the second sec	98: 400 400 Va Va 400 200 Specimen Urine Sed. Ventilation ra ocal exhaust venti mended exposure	2) ppm 3 mg/m3 2) ppm , Table 21) lue 2) ppm 2) ppm 3) ppm 4) ppm 4) tes should be matched to conditions. If lation, or other engineering controls to a limits. If exposure limits have not been
Canada. Saskatchewan OE Components Propan-2-ol (CAS 67-63-0) ogical limit values ACGIH Biological Exposur Components Propan-2-ol (CAS 67-63-0) * - For sampling details, plea ropriate engineering trols	e Indices Value 40 mg/l ase see the sou Good gene applicable, maintain air established s, such as pers	Determinant Acetone Ince document. rail ventilation should be ususe process enclosures, leborne levels below recom maintain airborne levels	98: 400 200 200 200 200 200 200 200 200 200	2) ppm 3 mg/m3 2) ppm , Table 21) lue 2) ppm 2) ppm 3) ppm 4) ppm 5) ppm 4) tes should be matched to conditions. If lation, or other engineering controls to a limits. If exposure limits have not bee
Canada. Saskatchewan OE Components Propan-2-ol (CAS 67-63-0) ogical limit values ACGIH Biological Exposur Components Propan-2-ol (CAS 67-63-0) * - For sampling details, plea ropriate engineering trols vidual protection measures Eye/face protection	e Indices Value 40 mg/l ase see the sou Good gene applicable, maintain air established s, such as pers Wear safety Wear appro	Determinant Acetone urce document. ral ventilation should be us ventilation should be us borne levels below recom maintain airborne levels sonal protective equipm y glasses with side shields opriate chemical resistant grainutes. Minimum glove from	98: 400 200 200 200 200 200 200 200 200 200	2) ppm 3 mg/m3 2) ppm , Table 21) lue 2) ppm 2) ppm 2) ppm 3 5 5 5 5 5 5 5 5 5 5 5 5 5
Canada. Saskatchewan OE Components Propan-2-ol (CAS 67-63-0) ogical limit values ACGIH Biological Exposur Components Propan-2-ol (CAS 67-63-0) * - For sampling details, plea ropriate engineering trols vidual protection measures Eye/face protection Skin protection	e Indices Value 40 mg/l ase see the sou Good gener applicable, maintain air established s, such as pers Wear safety Wear appro time of 480 drying of sk	Determinant Acetone Ince document. ral ventilation should be usue process enclosures, letorne levels below recome, maintain airborne levels sonal protective equipm y glasses with side shields opriate chemical resistant eminutes. Minimum glove fin.	98: 400 200 200 200 200 200 200 200 200 200	2) ppm 3 mg/m3 2) ppm , Table 21) lue 2) ppm 2) ppm 2) ppm 3 5 5 5 5 5 5 5 5 5 5 5 5 5
Canada. Saskatchewan OF Components Propan-2-ol (CAS 67-63-0) ogical limit values ACGIH Biological Exposur Components Propan-2-ol (CAS 67-63-0) * - For sampling details, pleat propriate engineering trols vidual protection measures Eye/face protection Skin protection Hand protection	re Indices Value 40 mg/l ase see the sou Good gene applicable, maintain air established s, such as pers Wear safety Wear appro time of 480 drying of sk Wear suitab	Determinant Acetone Indext and selection of the selection of	98: 400 200 200 200 200 200 200 200 200 200	2) ppm 3 mg/m3 2) ppm , Table 21) lue 2) ppm 2) ppm 3) ppm 4) ppm 4) tes should be matched to conditions. If lation, or other engineering controls to a limits. If exposure limits have not been

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. When using, do not eat, drink or smoke. Private clothes and working clothes should be kept separately.

9. Physical and chemical properties

,	•
Appearance	
Physical state	Liquid.
Form	Liquid.
Colour	Colourless.
Odour	Characteristic.
Odour threshold	Not determined.
рН	8.5 (20°C) DIN 19268
Melting point/freezing point	Not determined.
Initial boiling point and boiling range	100 °C (212 °F)
Flash point	> 65.0 °C (> 149.0 °F)
Evaporation rate	Not determined.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not determined.
Flammability limit - upper (%)	Not determined.
Vapour pressure	23 hPa (20 °C)
Vapour density	Not determined.
Solubility(ies)	
Solubility (water)	Soluble.
Partition coefficient (n-octanol/water)	Not applicable, product is a mixture.
Auto-ignition temperature	Not determined.
Decomposition temperature	Not determined.
Viscosity	Not available.
Other information	
Density	1.00 g/cm3 (20 °C) DIN 51757
Kinematic viscosity	Not determined.
Particle size	Not applicable, material is a liquid.
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidising agents.
Hazardous decomposition products	No hazardous decomposition products are known.
11 Toxicological informat	ion

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	May cause an allergic skin reaction. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the	May cause an allergic skin reaction. Dermatitis. Rash.

physical, chemical and toxicological characteristics

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
Propan-2-ol (CAS 67-63-0)	openies	
Acute		
Dermal		
LD50	Rabbit	16.4 mg/kg, 24 Hours
Inhalation		
Vapour		
LC50	Rat	> 10000 ppm, 6 Hours
Oral		
LD50	Rat	5840 mg/kg bw/day
Skin corrosion/irritation	Prolonged or repeated contact	t may dry skin and cause irritation.
Serious eye damage/eye rritation	Direct contact with eyes may	cause temporary irritation.
Respiratory or skin sensitisation		
Respiratory sensitisation	Not a respiratory sensitiser.	
Skin sensitisation	May cause an allergic skin re	action.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Not classifiable as to carcinogenicity to humans.	
ACGIH Carcinogens		
Propan-2-ol (CAS 67-63- Canada - Manitoba OELs: c	,	A4 Not classifiable as a human carcinogen.
Propan-2-ol (CAS 67-63-	,	Not classifiable as a human carcinogen.
	Evaluation of Carcinogenicity	
Propan-2-ol (CAS 67-63-		3 Not classifiable as to carcinogenicity to humans.
Reproductive toxicity		o cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be harmful.	
Further information	No other specific acute or chi	onic health impact noted.
12. Ecological informatior	ı	
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.	
Components	Species	Test Results

Aquatic			
Crustacea	LC50	Daphnia magna	> 10000 mg/l, 24 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	9640 - 10000 mg/l, 96 hours

Persistence and degradability	The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.
Bioaccumulative potential	

Partition coefficient n-octanol / water (log Kow) Propan-2-ol (CAS 67-63-0)		0.05
Mobility in soil	No data available.	
Other adverse effects	No data available.	

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

ΙΑΤΑ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable. Basel Convention

Not applicable.

16. Other information

Revision date	-
Version No.	01
List of abbreviations	LC50: Lethal Concentration, 50%. LD50: Lethal Dose, 50%. IATA: International Air Transport Association. IMDG Code: International Maritime Dangerous Goods Code. STEL: Short-Term Exposure Limit. TDG: Transportation of Dangerous Goods. TWA: Time Weighted Average Value.
References	Registry of Toxic Effects of Chemical Substances (RTECS) HSDB® - Hazardous Substances Data Bank
Disclaimer	Husqvarna AB cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.