SAFETY DATA SHEET



1. Identification

Product identifier Husqvarna Foam Air Filter Oil

Other means of identification

Product code 593153401

Recommended use Filter lubricant.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information
Supplier Husqvarna Group

Address 9335 Harris Corners Parkway

Charlotte, NC 28269

USA

Telephone number 800-487-5951

Emergency telephone +1-760-476-3961 (Access code 333721)

number

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Not classified.

Environmental hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statements

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	
Distillates (petroleum),	64742-54-7	> 90
hydrotreated heavy paraffinic		

Composition comments All concentrations are in percent by weight. Components not listed are either non-hazardous or are

below reportable limits.

IP346 method DMSO extract for base oil substances: <3.0%.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important Direct contact with eyes may cause temporary irritation. Repeated exposure may cause skin

symptoms/effects, acute and dryness or cracking.

delayed

Husqvarna Foam Air Filter Oil SDS Canada

942411 Version #: 01 Revision date: - Issue date: 02-March-2018

Indication of immediate medical attention and special treatment needed

General information

Treat symptomatically.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed. Do not direct solid water stream or foam into hot, burning pools; this may cause frothing and increase fire intensity.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. Do not point solid water stream directly into burning oil to avoid spreading.

Specific methods

General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

Will burn if involved in a fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Clean contaminated area with oil-removing material.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid direct contact with eyes and prolonged skin exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. The handling temperature should not exceed 140°F/60°C. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Keep away from heat, sparks and open flame. Store away from incompatible materials (see section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Product	Туре	Value	Form
oil mist (Mineral)	TWA	5 mg/m3	Inhalable fraction.
Canada Alberta OELs (Occur	sational Haalth & Cafaty Code Cal	andula 4 Table 2\	
, ,	pational Health & Safety Code, Scl Type	Value	Form
Product oil mist (Mineral)		•	Form Mist.

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Product	Туре	Value	Form
oil mist (Mineral)	TWA	1 mg/m3	Mist.

Husqvarna Foam Air Filter Oil SDS Canada

942411 Version #: 01 Revision date: - Issue date: 02-March-2018

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) **Product Form** Value Type oil mist (Mineral) TWA 5 mg/m3 Inhalable fraction. Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) **Product** Value Form **Type** TWA oil mist (Mineral) 5 mg/m3 Inhalable fraction. Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) **Product Type** Value **Form** oil mist (Mineral) **STEL** 10 mg/m3 Mist. **TWA** 5 mg/m3 Mist.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide easy access to water supply and eye wash facilities.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Wear appropriate chemical resistant gloves. Nitrile or neoprene gloves are recommended. Be Hand protection

aware that the liquid may penetrate the gloves. Frequent change is advisable. Suitable gloves can

be recommended by the glove supplier.

Other Wear suitable protective clothing. Use of an impervious apron is recommended. Protective clothing

should be chemical/oil resistant.

If engineering controls do not maintain airborne concentrations below recommended exposure Respiratory protection

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Selection and use of respiratory protective equipment should be in accordance with OSHA General Industry Standard 29 CFR

1910.134; or in Canada with CSA Standard Z94.4.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Liquid. Physical state Form Clear liquid. Colour Colourless. Odour Mild oil odor. **Odour threshold** Not available. Ha Not available. Melting point/freezing point Not available. Initial boiling point and boiling Not available.

range

250.0 °C (482.0 °F) Cleveland open cup Flash point

Evaporation rate Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available. Explosive limit - upper

(%)

Not available.

Not available. Vapour pressure Not available. Vapour density

Husqvarna Foam Air Filter Oil SDS Canada

942411 Version # 01 Revision date: -Issue date: 02-March-2018 Relative density Not available.

Solubility(ies)

Solubility (water) Negligible.

Solubility (other) Miscible in most petroleum solvents.

Partition coefficient

(n-octanol/water)

Not available.

Auto-ignition temperatureNot available.Decomposition temperatureNot available.Viscosity248.8 cStViscosity temperature40 °C (104 °F)

Other information

Explosive properties Not explosive.

Oxidising properties Not oxidising.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials. Keep away from heat, sparks and open flame.

Incompatible materials Strong oxidising agents. Acids.

Hazardous decomposition

products

Thermal decomposition may produce smoke, oxides of carbon and lower molecular weight organic compounds whose composition have not been characterised. Sulfur dioxide. Nitrogen oxides.

Hydrocarbons. Aldehydes.

11. Toxicological information

Information on likely routes of exposure

Inhalation Inhalation of oil mist or vapours formed during heating of the product will irritate the respiratory

system and provoke coughing. Prolonged inhalation may be harmful.

Skin contactRepeated exposure may cause skin dryness or cracking. **Eye contact**Direct contact with eyes may cause temporary irritation.

Ingestion May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation. Repeated exposure may cause skin

dryness or cracking.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Product Species Test Results

Husqvarna Foam Air Filter Oil (CAS Mixture)

Acute Dermal

LD50 > 5000 mg/kg

Inhalation Vapour

LD50 > 20 mg/l

Oral

LD50 > 5000 mg/kg

Skin corrosion/irritationRepeated exposure may cause skin dryness or cracking. **Serious eye damage/eye**Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitisation

Respiratory sensitisation Not a respiratory sensitiser.

Skin sensitisation This product is not expected to cause skin sensitisation.

Husqvarna Foam Air Filter Oil SDS Canada

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

ACGIH Carcinogens

Distillates (petroleum), hydrotreated heavy paraffinic

A4 Not classifiable as a human carcinogen.

(CAS 64742-54-7)

Canada - Manitoba OELs: carcinogenicity

Distillates (petroleum), hydrotreated heavy paraffinic Not classifiable as a human carcinogen.

(CAS 64742-54-7)

IARC Monographs. Overall Evaluation of Carcinogenicity

Distillates (petroleum), hydrotreated heavy paraffinic 3 Not classifiable as to carcinogenicity to humans.

(CAS 64742-54-7)

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

Further information Repeated and prolonged overexposure to oil mists may result in droplet deposition, oil granuloma

formation, inflammation and increased incidence of infection in the respiratory tract.

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity**

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability This product is partially biodegradable. No data available on bioaccumulation. Bioaccumulative potential

Mobility in soil The product is insoluble or slightly soluble in water.

Other adverse effects Oil spills are generally hazardous to the environment. The product contains volatile organic

compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Dispose in accordance with all applicable regulations. Local disposal regulations

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

5/6

disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not established.

the IBC Code

15. Regulatory information

This product has been classified in accordance with the hazard criteria of the HPR and the SDS Canadian regulations

contains all the information required by the HPR.

Husqvarna Foam Air Filter Oil SDS Canada

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or regionInventory nameOn inventory (yes/no)*CanadaDomestic Substances List (DSL)YesCanadaNon-Domestic Substances List (NDSL)NoUnited States & Puerto RicoToxic Substances Control Act (TSCA) InventoryYes

16. Other information

Issue date 02-March-2018

Revision date - Version No. 01

Disclaimer Husgvarna Group cannot anticipate all conditions under which this information and its product, or

the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the

sheet was written based on the best knowledge and experience currently available.

Husqvarna Foam Air Filter Oil SDS Canada

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).