SAFETY DATA SHEET

Husqvarna[®]

1. Identification

Other means of identificationProduct code593153503Recommended useEngine oil.Recommended restrictionsNone known.Manufacturer/Importer/Supplei>Jstributor informationSupplierHusqvarna GroupAddress9335 Harris Corners ParkwayCharlotte, NC 28269USATelephone number800-487-5951Emergency telephone number+1-760-476-3961 (Access code 333721)
Recommended useEngine oil.Recommended restrictionsNone known.Manufacturer/Importer/Supplier/Supplier/Supplier/IterationSupplierHusqvarna GroupAddress9335 Harris Corners Parkway Charlotte, NC 28269 USATelephone number800-487-5951Emergency telephone number+1-760-476-3961 (Access code 333721)
Recommended restrictionsNone known.Manufacturer/Importer/Supplier/Supplier/SupplierIntroductor informationSupplierHusqvarna GroupAddress9335 Harris Corners Parkway Charlotte, NC 28269 USATelephone number800-487-5951Emergency telephone number+1-760-476-3961 (Access code 333721)
Manufacturer/Importer/Supplier/Distributor informationSupplierHusqvarna GroupAddress9335 Harris Corners Parkway Charlotte, NC 28269 USATelephone number800-487-5951Emergency telephone number+1-760-476-3961 (Access code 333721)
SupplierHusqvarna GroupAddress9335 Harris Corners Parkway Charlotte, NC 28269 USATelephone number800-487-5951Emergency telephone number+1-760-476-3961 (Access code 333721)
Address9335 Harris Corners Parkway Charlotte, NC 28269 USATelephone number800-487-5951Emergency telephone number+1-760-476-3961 (Access code 333721)
Charlotte, NC 28269 USA Telephone number 800-487-5951 Emergency telephone +1-760-476-3961 (Access code 333721) number
USA Telephone number 800-487-5951 Emergency telephone +1-760-476-3961 (Access code 333721) number
Telephone number 800-487-5951 Emergency telephone +1-760-476-3961 (Access code 333721) number
Emergency telephone +1-760-476-3961 (Access code 333721) number
number
2. Hazard(s) identification
Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.
Label elements
Hazard symbol None.
Signal word None.
Hazard statement The mixture does not meet the criteria for classification.
Precautionary statements
Prevention Observe good industrial hygiene practices.
Response Wash hands after handling.
Store away from incompatible materials.
Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.
Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name		CAS number	%
Distillates (petroleum), hydrotreated heavy paraffinic		64742-54-7	> 90
Mineral oil		Various	1 - 3
Composition comments	All concentrations are in percent by weight. Components not listed are either non-hazardous or are below reportable limits. IP346 method DMSO extract for base oil substances: <3.0%.		
4. First-aid measures			
Inhalation	Move to fresh air. Call a physician if sym	ptoms develop or persist.	
Skin contact	Wash off with soap and water. Get medi If product is injected into or under the sk appearance of the wound or its size, the as a surgical emergency. Even though in minimal or absent, early surgical treatment ultimate extent of injury.	in, or into any part of the body, reg individual should be evaluated im nitial symptoms from high pressure	pardless of the mediately by a physiciar injection may be
Husquarna 5W-30 Premium 4 Stroke			SDS Canada

Eye contact	Rinse with water. Get medical attention if irritation develops and persists.		
Ingestion	Rinse mouth. Get medical attention if symptoms occur.		
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation. Repeated exposure may cause skin dryness or cracking.		
Indication of immediate medical attention and special treatment needed	Treat symptomatically. HIGH PRESSURE SKIN INJECTION: Physician must be familiar with local procedures for treatment of this type of wound; incision, irrigation, removal of all necrotic tissue and open wound dressing.		
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.		
5. Fire-fighting measures			
Suitable extinguishing media	Foam. Dry chemical powder. Carbon dioxide (CO2).		
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.		
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed. Do not direct solid water stream or foam into hot, burning pools; this may cause frothing and increase fire intensity.		
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.		
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. Do not point solid water stream directly into burning oil to avoid spreading.		
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.		

General fire hazards

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for	Prevent product from entering drains.
containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Clean contaminated area with oil-removing material.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Avoid direct contact with eyes and prolonged skin exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. The handling

Will burn if involved in a fire.

Conditions for safe storage, Si including any incompatibilities

temperature should not exceed 140°F/60°C. Observe good industrial hygiene practices. Store in original tightly closed container. Keep away from heat, sparks and open flame. Store away from incompatible materials (see section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Product	Туре	Value	Form
oil mist (Mineral)	mist (Mineral) TWA		Inhalable fraction.
Canada. Alberta OELs (Occu Product	pational Health & Safety Code, Scl Type	hedule 1, Table 2) Value	Form
		· · · ·	Form Mist.

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Product Type Val oil mist (Mineral) TWA 5 m Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Product Type Val oil mist (Mineral) TWA 5 m Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational h Product Type Val oil mist (Mineral) STEL 10 oil mist (Mineral) STEL 10 rubation (Mineral) No biological exposure limits noted for the ingredient(s) Good general ventilation (typically 10 air changes per h should be matched to conditions. If applicable, use proto or or other engineering controls to maintain airborne levels exposure limits have not been established, maintain air easy access to water supply and eye wash facilities. dividual protection measures, such as personal protective equipment Eye/face protection Wear safety glasses with side shields (or goggles). Skin protection Hand protection Wear appropriate chemical resistant gloves. Nitrile or nu aware that the liquid may penetrate the gloves. Frequer be recommended by the glove supplier. Other Wear suitable protective clothing. Use of an impervious should be chemical/oil resistant. Respiratory protection If engineering controls do not maintain airborne concen limits (where applicable) or to an acceptable level (Value	Form
ProductTypeValoil mist (Mineral)TWA5 mCanada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)ProductTypeProductTypeValoil mist (Mineral)TWA5 mCanada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational hTypeValoil mist (Mineral)STEL10TWA5 mCondical limit valuesNo biological exposure limits noted for the ingredient(s)porporiate engineering ontrolsSocial exposure limits noted for the ingredient(s)Good general ventilation (typically 10 air changes per h should be matched to conditions. If applicable, use proc or other engineering controls to maintain airbore levels exposure limits have not been established, maintain air easy access to water supply and eye wash facilities.dividual protection measures, such as personal protective equipment Eye/face protectionWear appropriate chemical resistant gloves. Nitrile or n aware that the liquid may penetrate the gloves. Frequer be recommended by the glove supplier.OtherWear suitable protective clothing. Use of an impervious should be chemical/oil resistant.Respiratory protectionIf engineering controls do not maintain airborne concene limits (where applicable) or to an acceptable level (in co- been established), an approved respirator must be worn protective clothing. Ador smoking. Routinely equipment to remove contaminants.Physical and chemical properties pearanceAlways observe good personal hygiene measures, such and before eating, drinking, and/or smoking. Routinely equipment to remove contaminants.Physical	1 mg/m3	Mist.
Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) ProductYuaProductTypeValoil mist (Mineral)TWA5 mCanada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational h ProductTypeValoil mist (Mineral)STEL10oil mist (Mineral)STEL10TWA5 mtological limit values porporiate engineering ontrolsNo biological exposure limits noted for the ingregetent(s) Good general ventilation (typically 10 air changes per h should be matched to conditions. If applicable, use proc or other engineering controls to maintain airborne levels exposure limits have not been established, maintain air easy access to water supply and eye wash facilities.dividual protection measures, such as personal protective equipment Eye/face protectionWear appropriate chemical resistant gloves. Nitrile or n aware that the liquid may penetrate the gloves. Frequer be recommended by the glove supplier.OtherWear appropriate chemical resistant gloves. Streluer be recommended by the glove supplier.OtherWear appropriate chemical resistant.Respiratory protection Imits (where applicable) or to an acceptable level (in cc been established), an approved respirator must be worn protective equipment should be in accordance with OSI 1910.134; or in Canada with CSA Standard Z94.4.Thermal hazardsAlways observe good personal hygiene measures, suct and before eating, drinking, and/or smoking. Routinely equipment to remove contaminants Physical and Chemical properties ppearance Physical state FormLiquid.	Act) Value	Form
ProductTypeValoil mist (Mineral)TWA5 mCanada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational h ProductTypeValoil mist (Mineral)STEL10oil mist (Mineral)STEL10TWA5 miological limit valuesNo biological exposure limits noted for the ingredient(s)ppropriate engineeringGood general ventilation (typically 10 air changes per h should be matched to conditions. If applicable, use proc or other engineering controls to maintain airbiorne levels 	5 mg/m3	Inhalable fraction.
Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational h ProductYaloil mist (Mineral)STEL10iological limit values porporiate engineering ontrolsNo biological exposure limits noted for the ingredient(s) Good general ventilation (typically 10 air changes per h should be matched to conditions. If applicable, use proc or other engineering controls to maintain airborne levels exposure limits have not been established, maintain air easy access to water supply and eye wash facilities.dividual protection measures, such as personal protective equipment Eye/face protectionWear appropriate chemical resistant gloves. Nitrile or nu aware that the liquid may penetrate the gloves. Frequer be recommended by the glove supplier.OtherWear appropriate chemical resistant gloves. Nitrile or nu aware that the liquid may penetrate the gloves. Frequer be recommended by the glove supplier.OtherWear suitable protective clothing. Use of an impervious should be chemical/oil resistant.Respiratory protectionIf engineering controls do not maintain airborne concent limits (where applicable) or to an acceptable level (in co been established), an approved respirator must be worn protective equipment should be in accordance with OSI 1910.134; or in Canada with CSA Standard Z94.4.Thermal hazardsWear appropriate thermal protective clothing, when nec and before eating, drinking, and/or smoking. Routinely equipment to remove contaminants Physical and chemical properties ppearance Physical stateLiquid.FormLiquid.	ents) Value	Form
ProductTypeValoil mist (Mineral)STEL10TWA5 mbological limit valuesNo biological exposure limits noted for the ingredient(s)popropriate engineering ontrolsGood general ventilation (typically 10 air changes per h should be matched to conditions. If applicable, use proc or other engineering controls to maintain air 	5 mg/m3	Inhalable fraction.
TWA5 mtological limit values porporriate engineering ontrolsNo biological exposure limits noted for the ingredient(s) Good general ventilation (typically 10 air changes per h should be matched to conditions. If applicable, use pro- or other engineering controls to maintain airborne levels exposure limits have not been established, maintain air easy access to water supply and eye wash facilities.dividual protection measures, such as personal protective equipment Eye/face protection Hand protection Hand protectionWear appropriate chemical resistant gloves. Nitrile or m aware that the liquid may penetrate the gloves. Frequer be recommended by the glove supplier.OtherWear suitable protective clothing. Use of an impervious should be chemical/oil resistant.Respiratory protection emeral hazardsIf engineering controls do not maintain airborne concen limits (where applicable) or to an acceptable level (in co been established), an approved respirator must be worn protective equipment should be in accordance with OSI 1910.134; or in Canada with CSA Standard Z94.4.Thermal hazardsWear appropriate thermal protective clothing, when nec and before eating, drinking, and/or smoking. Routinely equipment to remove contaminants.Physical and chemical properties peerance Physical stateLiquid.	ional health a Value	nd safety) Form
ological limit values opropriate engineering ontrolsNo biological exposure limits noted for the ingredient(s) Good general ventilation (typically 10 air changes per h should be matched to conditions. If applicable, use prod or other engineering controls to maintain airborne levels exposure limits have not been established, maintain air 	10 mg/m3	Mist.
Oppopriate engineering introlsGood general ventilation (typically 10 air changes per h should be matched to conditions. If applicable, use prod or other engineering controls to maintain airborne levels exposure limits have not been established, maintain air easy access to water supply and eye wash facilities.dividual protection measures, such as personal protective equipment Eye/face protectionWear safety glasses with side shields (or goggles).Skin protection Hand protection Hand protectionWear appropriate chemical resistant gloves. Nitrile or no aware that the liquid may penetrate the gloves. Frequer be recommended by the glove supplier.OtherWear suitable protective clothing. Use of an impervious should be chemical/oil resistant.Respiratory protection Imits (where applicable) or to an acceptable level (in cc been established), an approved respirator must be worn protective equipment should be in accordance with OSI 1910.134; or in Canada with CSA Standard Z94.4.Thermal hazards emeral hygiene nsiderationsAlways observe good personal hygiene measures, suct and before eating, drinking, and/or smoking. Routinely equipment to remove contaminants.Physical and chemical properties opearance Physical stateLiquid.	5 mg/m3	Mist.
Introlsshould be matched to conditions. If applicable, use procorrest or other engineering controls to maintain airborne levels exposure limits have not been established, maintain air easy access to water supply and eye wash facilities.dividual protection measures, such as personal protective equipmentEye/face protectionEye/face protectionWear safety glasses with side shields (or goggles).Skin protectionHand protectionHand protectionWear appropriate chemical resistant gloves. Nitrile or maware that the liquid may penetrate the gloves. Frequer be recommended by the glove supplier.OtherWear suitable protective clothing. Use of an impervious should be chemical/oil resistant.Respiratory protectionIf engineering controls do not maintain airborne concen limits (where applicable) or to an acceptable level (in corrective equipment should be in accordance with OSI 1910.134; or in Canada with CSA Standard Z94.4.Thermal hazardsWear appropriate thermal protective clothing, when nece and before eating, drinking, and/or smoking. Routinely equipment to remove contaminants.Physical and chemical propertiesLiquid.FormLiquid.		
Skin protection Hand protection Hand protection Wear appropriate chemical resistant gloves. Nitrile or ma aware that the liquid may penetrate the gloves. Frequer be recommended by the glove supplier. Other Wear suitable protective clothing. Use of an impervious should be chemical/oil resistant. Respiratory protection If engineering controls do not maintain airborne concen limits (where applicable) or to an acceptable level (in composed respirator must be worn protective equipment should be in accordance with OSI 1910.134; or in Canada with CSA Standard Z94.4. Thermal hazards Wear appropriate thermal protective clothing, when nece eneral hygiene measures and before eating, drinking, and/or smoking. Routinely equipment to remove contaminants. Physical and chemical properties Liquid. Form Liquid.	itain airborne le ties.	
Hand protectionWear appropriate chemical resistant gloves. Nitrile or maware that the liquid may penetrate the gloves. Frequer be recommended by the glove supplier.OtherWear suitable protective clothing. Use of an impervious should be chemical/oil resistant.Respiratory protectionIf engineering controls do not maintain airborne concen limits (where applicable) or to an acceptable level (in corbeen established), an approved respirator must be worn protective equipment should be in accordance with OSI 1910.134; or in Canada with CSA Standard Z94.4.Thermal hazardsAlways observe good personal hygiene measures, such and before eating, drinking, and/or smoking. Routinely equipment to remove contaminants.Physical and chemical propertiespropertiesprearanceLiquid.	es).	
Respiratory protectionIf engineering controls do not maintain airborne concen limits (where applicable) or to an acceptable level (in co been established), an approved respirator must be worn protective equipment should be in accordance with OSI 		
Imits (where applicable) or to an acceptable level (in column to be en established), an approved respirator must be worn protective equipment should be in accordance with OSI 1910.134; or in Canada with CSA Standard Z94.4.Thermal hazardsWear appropriate thermal protective clothing, when nece Always observe good personal hygiene measures, such and before eating, drinking, and/or smoking. Routinely equipment to remove contaminants.Physical and chemical properties opearance FormLiquid.	ervious apron i	s recommended. Protective clothing
eneral hygiene Always observe good personal hygiene measures, such and before eating, drinking, and/or smoking. Routinely equipment to remove contaminants. Physical and chemical properties opearance Physical state Liquid. Form Liquid.	el (in countries be worn. Selec /ith OSHA Gen	where exposure limits have not stion and use of respiratory
onsiderations and before eating, drinking, and/or smoking. Routinely equipment to remove contaminants. Physical and chemical properties opearance Physical state Liquid. Form Liquid.	nen necessary.	
ppearance Physical state Form Liquid.		
Physical stateLiquid.FormLiquid.		
Physical stateLiquid.FormLiquid.		
Colour Ambor to brown		
Colour Amber to brown.		

Odour

рΗ

range

Flash point Evaporation rate

Odour threshold

Melting point/freezing point

Flammability (solid, gas)

Initial boiling point and boiling

Mild petroleum odour.

218.0 °C (424.4 °F) Cleveland open cup

Not available. Not available.

Not available.

Not available.

Not available. Not applicable.

Explosive limit – upper (%)	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Negligible.
Solubility (other)	Miscible in most petroleum solvents.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	62 cSt
Viscosity temperature	40 °C (104 °F)
Other information	
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.		
Chemical stability	Material is stable under normal conditions.		
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.		
Conditions to avoid	Contact with incompatible materials. Keep away from heat, sparks and open flame.		
Incompatible materials	Strong oxidising agents. Acids.		
Hazardous decomposition products	Thermal decomposition may produce smoke, oxides of carbon and lower molecular weight organic compounds whose composition have not been characterised. Phosphorus oxides. Sulfur dioxide. Nitrogen oxides. Hydrocarbons. Aldehydes. Fumes of metal oxides.		

11. Toxicological information

Information on likely routes of exposure

Inhalation	Inhalation of oil mist or vapours formed during heating of the product will irritate the respiratory system and provoke coughing. Prolonged inhalation may be harmful.
Skin contact	Repeated exposure may cause skin dryness or cracking.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause discomfort if swallowed.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation. Repeated exposure may cause skin dryness or cracking.

Information on toxicological effects

Acute toxicity	Not expected to be acutely toxic.		
Product	Species	Test Results	
Husqvarna 5W-30 Premium 4 S	Stroke Oil (CAS Mixture)		
Acute			
Dermal			
LD50		> 5000 mg/kg	
Inhalation			
Vapour			
LD50		> 20 mg/l	
Oral			
LD50		> 5000 mg/kg	
Skin corrosion/irritation	Repeated exposure may cause skin dryness or cracking.		

Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.		
Respiratory or skin sensitisation	า		
Respiratory sensitisation	Not a respiratory sensitiser.		
Skin sensitisation	This product is not expected to cause skin sensitisation.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	Not classifiable as to carcino	genicity to humans.	
ACGIH Carcinogens			
Distillates (petroleum), hy (CAS 64742-54-7)	hydrotreated heavy paraffinic A4 Not classifiable as a human carcinogen.		
Canada - Manitoba OELs: ca	arcinogenicity		
Distillates (petroleum), hy (CAS 64742-54-7)	i), hydrotreated heavy paraffinic Not classifiable as a human carcinogen.		
IARC Monographs. Overall	Evaluation of Carcinogenicity	1	
Distillates (petroleum), hy (CAS 64742-54-7)	vdrotreated heavy paraffinic 3 Not classifiable as to carcinogenicity to humans.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.		
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not an aspiration hazard.		
Chronic effects	Prolonged inhalation may be harmful.		
Further information	Repeated and prolonged overexposure to oil mists may result in droplet deposition, oil granuloma formation, inflammation and increased incidence of infection in the respiratory tract.		
	Used petrol engine oils have shown evidence of skin carcinogenic activity in laboratory tests when no effort was made to wash the oil off between applications. The relevance of these results to humans has not been fully established.		
12 Ecological information			

12. Ecological information

Ecotoxicity	Harmful to aquatic life with long lasting effects.			
Components		Species	Test Results	
Additive (CAS Proprietary)				
Aquatic				
Acute				
Crustacea	EC50	Daphnia	0.037 mg/l, 48 hours	
Chronic				
Crustacea	NOEC	Daphnia	0.0037 mg/l, 21 days	
Persistence and degradability	This produ	This product is partially biodegradable.		
Bioaccumulative potential	No data av	ailable on bioaccumulation	on.	
Mobility in soil	The produc	ct is insoluble or slightly s	oluble in water.	
Other adverse effects	Oil spills are generally hazardous to the environment. The product contains volatile organic compounds which have a photochemical ozone creation potential.			
13. Disposal consideration	ons			
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.			
Local disposal regulations	Dispose in accordance with all applicable regulations.			
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.			
Waste from residues / unused products	product res		regulations. Empty containers or liners may retain some its container must be disposed of in a safe manner (see:	

Husqvarna 5W-30 Premium 4 Stroke Oil

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

ΙΑΤΑ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established. Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

- Not applicable.
- **Rotterdam Convention**
- Not applicable.
- **Kyoto Protocol**

Not applicable.

- Montreal Protocol
- Not applicable.
- Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date	02-March-2018
Revision date	-
Version No.	01
Disclaimer	Husqvarna Group cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.