

1. Identification

Product identifier Husqvarna SAE 30 Premium 4 Stroke Oil

Other means of identification
Product code 593153502, 593988691

Recommended use Engine oil.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Supplier Husqvarna Group

Address 9335 Harris Corners Parkway
 Charlotte, NC 28269
 USA

Telephone number 800-487-5951

Emergency telephone number +1-760-476-3961 (Access code 333721)

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Not classified.

Environmental hazards Not classified.

Label elements

Hazard symbol None.

Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statements

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	> 90
Mineral oil	Various	1 - 3

Composition comments All concentrations are in percent by weight. Components not listed are either non-hazardous or are below reportable limits.
 IP346 method DMSO extract for base oil substances: <3.0%.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation. Repeated exposure may cause skin dryness or cracking.
Indication of immediate medical attention and special treatment needed	Treat symptomatically. HIGH PRESSURE SKIN INJECTION: Physician must be familiar with local procedures for treatment of this type of wound; incision, irrigation, removal of all necrotic tissue and open wound dressing.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed. Do not direct solid water stream or foam into hot, burning pools; this may cause frothing and increase fire intensity.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. Do not point solid water stream directly into burning oil to avoid spreading.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Will burn if involved in a fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Prevent product from entering drains. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Clean contaminated area with oil-removing material. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Avoid direct contact with eyes and prolonged skin exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. The handling temperature should not exceed 140°F/60°C. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store in original tightly closed container. Keep away from heat, sparks and open flame. Store away from incompatible materials (see section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Product	Type	Value	Form
oil mist (Mineral)	TWA	5 mg/m ³	Inhalable fraction.

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Product	Type	Value	Form
oil mist (Mineral)	STEL	10 mg/m ³	Mist.
	TWA	5 mg/m ³	Mist.

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Product	Type	Value	Form
oil mist (Mineral)	TWA	1 mg/m ³	Mist.

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Product	Type	Value	Form
oil mist (Mineral)	TWA	5 mg/m ³	Inhalable fraction.

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Product	Type	Value	Form
oil mist (Mineral)	TWA	5 mg/m ³	Inhalable fraction.

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Product	Type	Value	Form
oil mist (Mineral)	STEL	10 mg/m ³	Mist.
	TWA	5 mg/m ³	Mist.

Biological limit values	No biological exposure limits noted for the ingredient(s).
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide easy access to water supply and eye wash facilities.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves. Nitrile or neoprene gloves are recommended. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. Suitable gloves can be recommended by the glove supplier.
Other	Wear suitable protective clothing. Use of an impervious apron is recommended. Protective clothing should be chemical/oil resistant.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Selection and use of respiratory protective equipment should be in accordance with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Liquid.
Colour	Amber to brown.

Odour Mild petroleum odour.

Odour threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling range Not available.

Flash point 235.0 °C (455.0 °F) Cleveland open cup

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit – upper (%)	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Negligible.
Solubility (other)	Miscible in most petroleum solvents.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	79 cSt
Viscosity temperature	40 °C (104 °F)
Other information	
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials. Keep away from heat, sparks and open flame.
Incompatible materials	Strong oxidising agents. Acids.
Hazardous decomposition products	Thermal decomposition may produce smoke, oxides of carbon and lower molecular weight organic compounds whose composition have not been characterised. Phosphorus oxides. Sulfur dioxide. Nitrogen oxides. Hydrocarbons. Aldehydes. Fumes of metal oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Inhalation of oil mist or vapours formed during heating of the product will irritate the respiratory system and provoke coughing. Prolonged inhalation may be harmful.
Skin contact	Repeated exposure may cause skin dryness or cracking.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation. Repeated exposure may cause skin dryness or cracking.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Product	Species	Test Results
Husqvarna SAE 30 Premium 4 Stroke Oil (CAS Mixture)		
Acute		
Dermal		
	LD50	> 5000 mg/kg
Inhalation		
<i>Vapour</i>		
	LD50	> 20 mg/l
Oral		
	LD50	> 5000 mg/kg
Skin corrosion/irritation	Repeated exposure may cause skin dryness or cracking.	

Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitisation	
Respiratory sensitisation	Not a respiratory sensitiser.
Skin sensitisation	This product is not expected to cause skin sensitisation.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Not classifiable as to carcinogenicity to humans.
ACGIH Carcinogens	
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	A4 Not classifiable as a human carcinogen.
Canada - Manitoba OELs: carcinogenicity	
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	Not classifiable as a human carcinogen.
IARC Monographs. Overall Evaluation of Carcinogenicity	
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	3 Not classifiable as to carcinogenicity to humans.
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful.
Further information	Repeated and prolonged overexposure to oil mists may result in droplet deposition, oil granuloma formation, inflammation and increased incidence of infection in the respiratory tract. Used petrol engine oils have shown evidence of skin carcinogenic activity in laboratory tests when no effort was made to wash the oil off between applications. The relevance of these results to humans has not been fully established.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components		Species	Test Results
Additive (CAS Proprietary)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Daphnia	0.037 mg/l, 48 hours
<i>Chronic</i>			
Crustacea	NOEC	Daphnia	0.0037 mg/l, 21 days

Persistence and degradability This product is partially biodegradable.

Bioaccumulative potential No data available on bioaccumulation.

Mobility in soil The product is insoluble or slightly soluble in water.

Other adverse effects Oil spills are generally hazardous to the environment. The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information**TDG**

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

Canadian regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations**Stockholm Convention**

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date 02-March-2018

Revision date 05-March-2018

Version No. 02

Disclaimer

Husqvarna Group cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.