

SAFETY DATA SHEET

Section 1 - Identification

Product identifier Husqvarna AIR FILTER OIL SPRAY

Other means of identification

Product code 538 62 95-01 (200 ml)

Recommended use of the chemical and restrictions on use

Recommended use Lubricant
Restrictions on use All other uses.

Details of manufacturer or importer

Supplier Husqvarna Australia Pty Ltd

Address 4 Pioneer Avenue, Tuggerah NSW 2252

Country Australia

Telephone +61 2 4352 7400 Contact person Jason Bezzina

E-mail jason.bezzina@husqvarnagroup.com

Emergency Contact Poisons Information Centre; phone 13 12 26

Section 2 - Hazard(s) identification

Classification of the hazardous chemical

Physical hazards Aerosols Category 1

Health hazards Not classified.

Label elements, including precautionary statements

Hazard symbol(s)



Flame

Signal word Danger

Hazard statement(s) Extremely flammable aerosol. Pressurized container: May burst if heated.

Precautionary statement(s)

Prevention Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not

pierce or burn, even after use.

Response Not assigned.

Storage Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Not assigned.

Supplemental information None.

Other hazards which do not None

result in classification

None known.

Section 3 - Composition and information on ingredients

Mixture

Identity of chemical ingredients	CAS number and other unique identifiers	Concentration of ingredients
Diethoxymethane	462-95-3	25-40
Butane	106-97-8	15-25

Husqvarna AIR FILTER OIL SPRAY SDS Australia

Propane	74-98-6	10-15
Isobutane	75-28-5	5-10

Section 4 - First aid measures

Description of necessary first aid measures

Move to fresh air. Call a physician if symptoms develop or persist. Inhalation

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

Rinse with water. Get medical attention if irritation develops and persists. Eye contact In the unlikely event of swallowing contact a physician or poison control centre. Ingestion

Personal protection for first-aid

responders

Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

Treat symptomatically.

Symptoms caused by exposure

Medical attention and special

treatment

Direct contact with eyes may cause temporary irritation.

Section 5 - Firefighting measures

Extinguishing media

Suitable extinguishing

equipment

Powder. Carbon dioxide (CO2).

Unsuitable extinguishing

equipment

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose

holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Hazchem code

General fire hazards

Extremely flammable aerosol.

Specific methods

None.

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

Section 6 - Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Do not touch damaged containers or spilled material unless wearing appropriate protective

clothing.

For emergency responders

Keep unnecessary personnel away. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection,

see section 8 of the SDS.

Environmental precautions

Methods and materials for containment and cleaning up Avoid discharge into drains, water courses or onto the ground.

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Collect in a non-combustible container for prompt disposal.

Small Liquid Spills: Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Clean surface thoroughly to remove residual contamination.

For waste disposal, see section 13 of the SDS.

Section 7 - Handling and storage

Precautions for safe handling

Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Keep away from heat, sparks and open flame. Store in tightly closed container. Store away from

incompatible materials (see section 10 of the SDS).

Section 8 - Exposure controls and personal protection

Control parameters Follow standard monitoring procedures.

Occupational exposure limits

Australia. National Workplace OELs (Workplace Exposure Standards for Airborne Contaminants, Appendix A)

Components	Туре	Value	
Butane (CAS 106-97-8)	TWA	1900 mg/m3	
		800 ppm	
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	
Butane (CAS 106-97-8)	STEL	1000 ppm	
Isobutane (CAS 75-28-5)	STEL	1000 ppm	
UK. EH40 Workplace Exposure L	imits (WELs)		
Components	Туре	Value	
Butane (CAS 106-97-8)	STEL	1810 mg/m3	
		750 ppm	
	TWA	1450 mg/m3	
		600 ppm	

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds

in the Work Area (DFG)

Components	Туре	Value	
Butane (CAS 106-97-8)	TWA	2400 mg/m3	
		1000 ppm	
Isobutane (CAS 75-28-5)	TWA	2400 mg/m3	
		1000 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	

Biological limit values No biological exposure limits noted for the ingredient(s).

Control banding Follow standard monitoring procedures.

Good general ventilation should be used. Ventilation rates should be matched to conditions. If **Engineering controls**

applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been

established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment (PPE)

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Wear appropriate chemical resistant gloves. Nitrile gloves are recommended. Hand protection

Other Wear suitable protective clothing.

In case of inadequate ventilation or risk of inhalation of vapours, use suitable respiratory Respiratory protection

equipment with combination filter.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

When using do not smoke. Always observe good personal hygiene measures, such as washing Hygiene measures

after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

Section 9 - Physical and chemical properties

Liquid. Physical state **Form** Aerosol.

Husqvarna AIR FILTER OIL SPRAY SDS Australia ColourColourless.OdourNot relevant.Odour thresholdNot available.

pH Not relevant, due to the form of the product in its manufactured and shipped state.
 Melting point/freezing point Not relevant, due to the form of the product in its manufactured and shipped state.
 Boiling point and boiling range Not relevant, due to the form of the product in its manufactured and shipped state.

Flash point Not applicable: aerosol spray can.

Evaporation rate Not relevant, due to the form of the product in its manufactured and shipped state.

Flammability (solid, gas) Extremely flammable aerosol.

Upper/lower explosive limits

Explosion limit - lower (%) Not relevant, due to the form of the product in its manufactured and shipped state.

Vapour pressure Not relevant, due to the form of the product in its manufactured and shipped state.

Vapour density Not relevant, due to the form of the product in its manufactured and shipped state.

Not relevant, due to the form of the product in its manufactured and shipped state.

Relative density

Not relevant, due to the form of the product in its manufactured and shipped state.

Solubility

Solubility (water) Not relevant, due to the form of the product in its manufactured and shipped state.

Partition coefficient: Not relevant, due to the form of the product in its manufactured and shipped state.

n-octanol/water

Auto-ignition temperature

Not relevant, due to the form of the product in its manufactured and shipped state.

Not relevant, due to the form of the product in its manufactured and shipped state.

ViscosityNot relevant, due to the form of the product in its manufactured and shipped state.

Particle characteristics Not available.

Data relevant with regard to No relevant additional information available. physical hazard classes

Section 10 - Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materialsStrong oxidising agents. Chlorine. Fluorine. Nitrates.Hazardous decompositionNo hazardous decomposition products are known.

products

Section 11 - Toxicological information

Information on possible routes of exposure

Inhalation Breathing of high concentrations may cause dizziness, light-headedness, headache, nausea and

loss of co-ordination. Continued inhalation may result in unconsciousness.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Early onset symptoms related

to exposure

Direct contact with eyes may cause temporary irritation.

Delayed health effects from

exposure

Chronic effects are not expected when this product is used as intended.

Acute toxicity Not expected to be acutely toxic.

Husqvarna AIR FILTER OIL SPRAY SDS Australia

Components	Species	Test Results
Butane (CAS 106-97-8)		
<u>Acute</u>		
Inhalation		
LC50	Rat	658 mg/l, 4 Hours
Isobutane (CAS 75-28-5)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	520400 - 539600 ppm, 2 hours
		1237 mg/l, 2 hours
	Rat	1443 - 1443 mg/l, 15 minutes
		800000 ppm, 15 minutes
Propane (CAS 74-98-6)		
<u>Acute</u>		
Inhalation		
Gas		
LC50	Rat	> 80000 ppm, 15 Minutes
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitisation		
Respiratory sensitisation	Not a respiratory sensitiser.	
Skin sensitisation	This product is not expected to cause skin sensitisation.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Not classifiable as to carcinogenicity to humans.	
Reproductive toxicity	This product is not expected to cause reproductive of	or developmental effects.
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Other information	No data available.	
Section 12 - Ecological inf	ormation	

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment **Ecotoxicity**

Components		Species	Test Results
Isobutane (CAS 75-28-5)			
Aquatic			
Algae	EC50	Algae	> 7.71 - < 19.37 mg/l, 96 hours
Acute			
Crustacea	LC50	Aquatic invertebrates	> 14.22 - < 69.43 mg/l, 48 hours
Fish	LC50	Fish	> 24.11 - < 147.54 mg/l, 96 hours
ersistence and degradability	Volatile s	ubstances are degraded in the atmos	phere within a few days.
Bioaccumulative potential			
Partition coefficient			

n-octanol / water (log Kow)

Butane (CAS 106-97-8) 2.89 Isobutane (CAS 75-28-5) 2.76

No data available for this product. Mobility in soil

Other adverse effects No data available.

Husqvarna AIR FILTER OIL SPRAY SDS Australia

Section 13 - Disposal considerations

Disposal methodsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

Section 14 - Transport information

ADG

UN number 1950 UN proper shipping name AEROSOLS

Transport hazard class(es)

Class 2 Subsidiary risk -

Packing group Not assigned.

Environmental hazards No.

Hazchem code Not assigned.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

RID

UN number 1950

UN proper shipping name AEROSOLS, flammable

Transport hazard class(es)

Class 2
Subsidiary risk Label(s) 2.1

Packing group Not assigned.

Environmental hazards

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number 1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -

Packing group Not assigned.

Environmental hazards No. **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number 1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -

Packing group Not assigned.

Environmental hazards

Marine pollutant No. mS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to No.

Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

Section 15 - Regulatory information

Safety, health and environmental regulations

Husqvarna AIR FILTER OIL SPRAY

SDS Australia

National regulations

This Safety Data Sheet was prepared in accordance with Australia Model Code of Practice for the

preparation of Safety Data Sheets for Hazardous Chemicals.

The components of this product are listed, or are exempt from listing, on the Australian Inventory of Industrial Chemicals (AIIC)

Australia Medicines & Poisons Appendix E

Butane (CAS 106-97-8) Isobutane (CAS 75-28-5)

Australia Medicines & Poisons Schedule 5

Butane (CAS 106-97-8) Isobutane (CAS 75-28-5)

High Volume Industrial Chemicals (HVIC)

Butane (CAS 106-97-8) 100000 - 999999 TONNES See the regulation for additional

information.

10000 - 99999 TONNES See the regulation for additional Isobutane (CAS 75-28-5)

information.

100000 - 999999 TONNES See the regulation for additional Propane (CAS 74-98-6)

information.

Importation of Ozone Depleting Substances (Customs(Prohibited imports) Regulations 1956, Schedule 10, as amended)

National Pollutant Inventory (NPI) substance reporting list

Prohibited Carcinogenic Substances

Not regulated.

Prohibited Substances (National Model Regulation for the control of Workplace Hazardous Substances, Schedule 2 NOHSC:1005 (1994) as amended)

Not listed.

Restricted Carcinogenic Substances

Not regulated.

Restricted Importation of Organochlorine Chemicals (Customs(Prohibited Imports) Regulations 1956, Schedule 9)

Not listed.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

Section 16 - Any other relevant information

Issue date 02-March-2023

Revision date

Key abbreviations or acronyms AICIS: Australian Inventory of Industrial Chemicals.

used

ECHA: European Chemical Agency. References

Disclaimer Husqvarna AB cannot anticipate all conditions under which this information and its product, or the

products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the

sheet was written based on the best knowledge and experience currently available.

Husqvarna AIR FILTER OIL SPRAY Version #: 01 Revision date: -Issue date: 02-March-2023