

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

4.4. Droduct identifier	······································
1.1. Product identifier	Unamer VD® Curthetic
Trade name or designation of the mixture	Husqvarna XP® Synthetic
Registration number	-
Synonyms	None.
Product code	578 18 03-03 (0.1L), 578 18 03-07 (0.1L), 578 03 70-03 (1L), 578 03 71-03 (4L), 578 18 00-03 (10L), 578 18 04-03 (208L)
Issue date	12-February-2015
Version number	02
Revision date	13-December-2023
Supersedes date	12-February-2015
1.2. Relevant identified uses of	the substance or mixture and uses advised against
Identified uses	Lubrication of 2-stroke engine.
Uses advised against	All other uses.
1.3. Details of the supplier of the	e safety data sheet
Company name	Husqvarna UK Ltd
	Preston Road, Aycliffe Industrial Park
	Newton Aycliffe, County Durham, DL5 6UP
Telephone	+46 (0)36-14 65 00
Contact person	Accessory Department
E-mail	sds.info@husqvarnagroup.com
1.4. Emergency telephone number	+1-760-476-3961 (Access code 333721)
General emergency	112 or 999 SDS/Product information may not be available for the Emergency Service.
Non-emergency medical helpline	111 SDS/Product information may not be available for the Emergency Service.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

This mixture does not meet the criteria for classification according to Regulation (EC) 1272/2008 as amended.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Hazard pictograms	None.
Signal word	None.
Hazard statements	The mixture does not meet the criteria for classification.
Precautionary statements	
Prevention	Not assigned.
Response	Not assigned.
Storage	Not assigned.
Disposal	Not assigned.
Supplemental information on the label	EUH210 - Safety data sheet available on request.
2.3. Other hazards	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

5.2. Mixtures					
General information Chemical name	%		DEACH Deviation No.	Inday No	Notoo
Hydrocarbons, C11-C14, n-alk		CA3-NO. / EC NO.	REACH Registration No. 01-2119456620-43	Index No.	Notes
isoalkanes, cyclics, <2% arom	,	- 926-141-6	01-2119430020-43	-	
Classif	ication: Asp. Tox.	1;H304			
Distillates (petroleum), hydrotr	eated 2 - 5	64742-55-8	01-2119487077-29	649-468-00-3	
light paraffinic		265-158-7	0. 2 0		
Classif	ication: Asp. Tox.	1;H304			L
Phenol, butenylated aminated	0 - < 2.5	-	-	-	
polymer Classif	ication: Aquatic C	- hronic 2;H411			
Composition comments	The full text for a	ll H-statements is disr	played in section 16. All con	centrations are in	percent by
			concentrations are in perce		porcont by
SECTION 4: First aid meas	sures				
General information	Ensure that medi protect themselve		are of the material(s) involve	ed, and take preca	utions to
I.1. Description of first aid meas	ures				
Inhalation	Move to fresh air	. Call a physician if sy	mptoms develop or persist.		
Skin contact	Wash off with soa	ap and water. Get me	dical attention if irritation de	velops and persist	s.
Eye contact	Rinse with water.	Rinse with water. Get medical attention if irritation develops and persists.			
Ingestion	Rinse mouth. Get medical attention if symptoms occur.				
4.2. Most important symptoms and effects, both acute and delayed	Exposure may ca	ause temporary irritation	on, redness, or discomfort.		
4.3. Indication of any mmediate medical attention and special treatment needed	Treat symptomat	ically.			
SECTION 5: Firefighting m	easures				
General fire hazards		r explosion hazards n	oted.		
5.1. Extinguishing media					
Suitable extinguishing media	Water fog. Foam	. Dry chemical powde	r. Carbon dioxide (CO2).		
Unsuitable extinguishing media	Do not use water	jet as an extinguishe	r, as this will spread the fire		
5.2. Special hazards arising from the substance or mixture	During fire, gases	s hazardous to health	may be formed.		
5.3. Advice for firefighters					
Special protective equipment for firefighters	Self-contained br	eathing apparatus an	d full protective clothing mu	st be worn in case	of fire.
Special fire fighting procedures	Move containers from fire area if you can do so without risk.				
Specific methods	Use standard fire	fighting procedures a	nd consider the hazards of	other involved mat	erials.
SECTION 6: Accidental rel	ease measure	S			
6.1. Personal precautions, prote	ctive equipment a	nd emergency proc	edures		
For non-emergency personnel			void breathing mist/vapours		
For emergency responders	Keep unnecessa	ry personnel away. Fo	or personal protection, see s	section 8 of the SE	S.

6.2. Environmental precautions Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for	The product is immiscible with water and will spread on the water surface.				
containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.				
	•	Nipe up with absorbent mat ual contamination.	erial (e.g. cloth, fleece). C	lean surface thoroughly to	
	Never return	spills to original containers f	or re-use.		
6.4. Reference to other sections	For personal	protection, see section 8 of	the SDS. For waste dispo	sal, see section 13 of the SDS.	
SECTION 7: Handling and	storage				
7.1. Precautions for safe handling	Avoid prolonged exposure. Observe good industrial hygiene practices. Do not cut or weld on empty drums unless they are thoroughly cleaned. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or promptly disposed of.			ould be completely drained,	
7.2. Conditions for safe storage, including any incompatibilities	Store in tightly closed container. Store away from incompatible materials (see section 10 of the SDS).				
7.3. Specific end use(s)	Lubrication of	2-stroke engine. Observe i	ndustrial sector guidance	on best practices.	
SECTION 8: Exposure cor	ntrols/perso	nal protection			
8.1. Control parameters					
Occupational exposure limits					
UK. OELs. Workplace Expos Components	sure Limits (W	ELs) (EH40/2005 (Fourth E Type	Edition 2020)), Table 1 Value		
Dipropylene glycol monomethyl ether (CAS		TWA	308 mg/m3		
34590-94-8)			50 ppm		
Biological limit values	U U	exposure limits noted for the	e ingredient(s).		
Recommended monitoring procedures	Follow standa	ard monitoring procedures.			
procedures					
Darivad no offact lovals (DNELs)	۱ ۱				
Derived no effect levels (DNELs)				
General population)	Value	Assessment factor	Notes	
General population Components	-	Value	Assessment factor	Notes	
<u>General population</u> <u>Components</u> Distillates (petroleum), hydroti Long-term, Local, Inhalat	reated light para	affinic (CAS 64742-55-8) 1.19 mg/m3	75	Repeated dose toxicity	
General population Components Distillates (petroleum), hydrotu Long-term, Local, Inhalat Long-term, Systemic, Ora	reated light para	affinic (CAS 64742-55-8)			
<u>General population</u> <u>Components</u> Distillates (petroleum), hydroti Long-term, Local, Inhalat Long-term, Systemic, Ora	reated light para	affinic (CAS 64742-55-8) 1.19 mg/m3 0.74 mg/kg bw/day	75 120	Repeated dose toxicity Repeated dose toxicity	
General population Components Distillates (petroleum), hydrotr Long-term, Local, Inhalat Long-term, Systemic, Ora Workers Components	reated light para ion al	affinic (CAS 64742-55-8) 1.19 mg/m3 0.74 mg/kg bw/day Value	75	Repeated dose toxicity	
General population Components Distillates (petroleum), hydrotu Long-term, Local, Inhalat Long-term, Systemic, Ora Workers Components Distillates (petroleum), hydrotu Long-term, Local, Inhalat Long-term, Systemic, Den	reated light para ion al reated light para ion rmal	affinic (CAS 64742-55-8) 1.19 mg/m3 0.74 mg/kg bw/day Value affinic (CAS 64742-55-8) 5.58 mg/m3 0.97 mg/kg bw/day	75 120 Assessment factor 45 72	Repeated dose toxicity Repeated dose toxicity Notes Repeated dose toxicity Repeated dose toxicity	
General population Components Distillates (petroleum), hydrotr Long-term, Local, Inhalat Long-term, Systemic, Ora Workers Components Distillates (petroleum), hydrotr Long-term, Local, Inhalat Long-term, Systemic, Der Long-term, Systemic, Inh	reated light para ion al reated light para ion rmal alation	affinic (CAS 64742-55-8) 1.19 mg/m3 0.74 mg/kg bw/day Value affinic (CAS 64742-55-8) 5.58 mg/m3	75 120 Assessment factor 45	Repeated dose toxicity Repeated dose toxicity Notes Repeated dose toxicity	
General population Components Distillates (petroleum), hydrotr Long-term, Local, Inhalat Long-term, Systemic, Ora Workers Components Distillates (petroleum), hydrotr Long-term, Local, Inhalat Long-term, Systemic, Der Long-term, Systemic, Inh	reated light para ion al reated light para ion rmal alation	affinic (CAS 64742-55-8) 1.19 mg/m3 0.74 mg/kg bw/day Value affinic (CAS 64742-55-8) 5.58 mg/m3 0.97 mg/kg bw/day 2.73 mg/m3	75 120 Assessment factor 45 72 45	Repeated dose toxicity Repeated dose toxicity Notes Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity	
General population Components Distillates (petroleum), hydrotu Long-term, Local, Inhalat Long-term, Systemic, Ora Workers Components Distillates (petroleum), hydrotu Long-term, Local, Inhalat Long-term, Systemic, Deu Long-term, Systemic, Inh Predicted no effect concentration Components	reated light para ion al reated light para ion rmal alation ons (PNECs)	affinic (CAS 64742-55-8) 1.19 mg/m3 0.74 mg/kg bw/day Value affinic (CAS 64742-55-8) 5.58 mg/m3 0.97 mg/kg bw/day 2.73 mg/m3 Value	75 120 Assessment factor 45 72	Repeated dose toxicity Repeated dose toxicity Notes Repeated dose toxicity Repeated dose toxicity	
General population Components Distillates (petroleum), hydrotr Long-term, Local, Inhalat Long-term, Systemic, Ora Workers Components Distillates (petroleum), hydrotr Long-term, Local, Inhalat Long-term, Systemic, Dei Long-term, Systemic, Dei Long-term, Systemic, Inh Predicted no effect concentration Components Distillates (petroleum), hydrotr	reated light para ion al reated light para ion rmal alation ons (PNECs)	affinic (CAS 64742-55-8) 1.19 mg/m3 0.74 mg/kg bw/day Value affinic (CAS 64742-55-8) 5.58 mg/m3 0.97 mg/kg bw/day 2.73 mg/m3 Value affinic (CAS 64742-55-8)	75 120 Assessment factor 45 72 45	Repeated dose toxicity Repeated dose toxicity Notes Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity	
General population Components Distillates (petroleum), hydrotr Long-term, Local, Inhalat Long-term, Systemic, Ora Workers Components Distillates (petroleum), hydrotr Long-term, Systemic, Det Long-term, Systemic, Inh Predicted no effect concentration Components Distillates (petroleum), hydrotr Secondary poisoning	reated light para ion al reated light para ion rmal alation ons (PNECs) reated light para	affinic (CAS 64742-55-8) 1.19 mg/m3 0.74 mg/kg bw/day Value affinic (CAS 64742-55-8) 5.58 mg/m3 0.97 mg/kg bw/day 2.73 mg/m3 Value affinic (CAS 64742-55-8) 9.33 mg/kg	75 120 Assessment factor 45 72 45	Repeated dose toxicity Repeated dose toxicity Notes Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity	
General population Components Distillates (petroleum), hydrotr Long-term, Local, Inhalat Long-term, Systemic, Ora Workers Components Distillates (petroleum), hydrotr Long-term, Systemic, Det Long-term, Systemic, Det Long-term, Systemic, Inh Predicted no effect concentration Components Distillates (petroleum), hydrotr Secondary poisoning Exposure guidelines	reated light para ion al reated light para ion rmal alation ons (PNECs) reated light para Follow standa	affinic (CAS 64742-55-8) 1.19 mg/m3 0.74 mg/kg bw/day Value affinic (CAS 64742-55-8) 5.58 mg/m3 0.97 mg/kg bw/day 2.73 mg/m3 Value Affinic (CAS 64742-55-8)	75 120 Assessment factor 45 72 45	Repeated dose toxicity Repeated dose toxicity Notes Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity	
General population Components Distillates (petroleum), hydrota Long-term, Local, Inhalat Long-term, Systemic, Ora Workers Components Distillates (petroleum), hydrota Long-term, Local, Inhalat Long-term, Systemic, Dei Long-term, Systemic, Inh Predicted no effect concentration Components Distillates (petroleum), hydrota Secondary poisoning Exposure guidelines UK EH40 WEL: Skin designa	reated light para ion al reated light para ion rmal alation ons (PNECs) reated light para Follow standa ation	affinic (CAS 64742-55-8) 1.19 mg/m3 0.74 mg/kg bw/day Value affinic (CAS 64742-55-8) 5.58 mg/m3 0.97 mg/kg bw/day 2.73 mg/m3 Value affinic (CAS 64742-55-8) 9.33 mg/kg ard monitoring procedures.	75 120 Assessment factor 45 72 45 Assessment factor	Repeated dose toxicity Repeated dose toxicity Notes Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity Notes Oral	
General population Components Distillates (petroleum), hydrotu Long-term, Local, Inhalat Long-term, Systemic, Ora Workers Components Distillates (petroleum), hydrotu Long-term, Local, Inhalat Long-term, Systemic, Der Long-term, Systemic, Der Long-term, Systemic, Inh Predicted no effect concentration Components Distillates (petroleum), hydrotu Secondary poisoning Exposure guidelines UK EH40 WEL: Skin designa	reated light para ion al reated light para ion rmal alation ons (PNECs) reated light para Follow standa ation	affinic (CAS 64742-55-8) 1.19 mg/m3 0.74 mg/kg bw/day Value affinic (CAS 64742-55-8) 5.58 mg/m3 0.97 mg/kg bw/day 2.73 mg/m3 Value affinic (CAS 64742-55-8) 9.33 mg/kg	75 120 Assessment factor 45 72 45 Assessment factor	Repeated dose toxicity Repeated dose toxicity Notes Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity Notes Oral	
General population Components Distillates (petroleum), hydrota Long-term, Local, Inhalat Long-term, Systemic, Ora Workers Components Distillates (petroleum), hydrota Long-term, Local, Inhalat Long-term, Systemic, Dei Long-term, Systemic, Inh Predicted no effect concentration Components Distillates (petroleum), hydrota Secondary poisoning Exposure guidelines UK EH40 WEL: Skin designa	reated light para ion al reated light para ion rmal alation ons (PNECs) reated light para Follow standa ation methyl ether (Ca Good general applicable, us maintain airbo	affinic (CAS 64742-55-8) 1.19 mg/m3 0.74 mg/kg bw/day Value affinic (CAS 64742-55-8) 5.58 mg/m3 0.97 mg/kg bw/day 2.73 mg/m3 Value affinic (CAS 64742-55-8) 9.33 mg/kg ard monitoring procedures. AS 34590-94-8) Can be a Ventilation should be used. se process enclosures, local	75 120 Assessment factor 45 72 45 Assessment factor bsorbed through the skin. Ventilation rates should to exhaust ventilation, or ot nded exposure limits. If ex	Repeated dose toxicity Repeated dose toxicity Notes Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity Notes Oral	
General population Components Distillates (petroleum), hydrott Long-term, Local, Inhalat Long-term, Systemic, Ora Workers Components Distillates (petroleum), hydrott Long-term, Local, Inhalat Long-term, Systemic, Dei Long-term, Systemic, Dei Long-term, Systemic, Inh Predicted no effect concentration Components Distillates (petroleum), hydrott Secondary poisoning Exposure guidelines UK EH40 WEL: Skin designa Dipropylene glycol monor 8.2. Exposure controls Appropriate engineering controls	reated light para ion al reated light para ion rmal alation ons (PNECs) reated light para Follow standa ation methyl ether (Ca Good general applicable, us maintain airbo established, r	affinic (CAS 64742-55-8) 1.19 mg/m3 0.74 mg/kg bw/day Value affinic (CAS 64742-55-8) 5.58 mg/m3 0.97 mg/kg bw/day 2.73 mg/m3 Value affinic (CAS 64742-55-8) 9.33 mg/kg ard monitoring procedures. AS 34590-94-8) Can be a Ventilation should be used. se process enclosures, local orne levels below recommer maintain airborne levels to a	75 120 Assessment factor 45 72 45 Assessment factor bsorbed through the skin. Ventilation rates should to exhaust ventilation, or ot nded exposure limits. If ex	Repeated dose toxicity Repeated dose toxicity Notes Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity Notes Oral	
General population Components Distillates (petroleum), hydrotr Long-term, Local, Inhalat Long-term, Systemic, Ora Workers Components Distillates (petroleum), hydrotr Long-term, Local, Inhalat Long-term, Systemic, Der Long-term, Systemic, Der Long-term, Systemic, Inh Predicted no effect concentration Components Distillates (petroleum), hydrotr Secondary poisoning Exposure guidelines UK EH40 WEL: Skin designa Dipropylene glycol monor 8.2. Exposure controls Appropriate engineering	reated light para ion al reated light para ion rmal alation ons (PNECs) reated light para Follow standa ation methyl ether (C, Good general applicable, us maintain airbo established, r such as perso Personal prot	affinic (CAS 64742-55-8) 1.19 mg/m3 0.74 mg/kg bw/day Value affinic (CAS 64742-55-8) 5.58 mg/m3 0.97 mg/kg bw/day 2.73 mg/m3 Value affinic (CAS 64742-55-8) 9.33 mg/kg ard monitoring procedures. AS 34590-94-8) Can be a Ventilation should be used. se process enclosures, local orne levels below recommer maintain airborne levels to a	75 120 Assessment factor 45 72 45 Assessment factor bsorbed through the skin. Ventilation rates should the exhaust ventilation, or ot nded exposure limits. If ex n acceptable level.	Repeated dose toxicity Repeated dose toxicity Notes Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity Notes Oral	
General population Components Distillates (petroleum), hydrotu Long-term, Local, Inhalat Long-term, Systemic, Ora Workers Components Distillates (petroleum), hydrotu Long-term, Local, Inhalat Long-term, Systemic, Der Long-term, Systemic, Der Long-term, Systemic, Inh Predicted no effect concentration Components Distillates (petroleum), hydrotu Secondary poisoning Exposure guidelines UK EH40 WEL: Skin designa Dipropylene glycol monor 8.2. Exposure controls Appropriate engineering controls	reated light para ion al reated light para ion rmal alation ons (PNECs) reated light para Follow standa ation methyl ether (C, Good general applicable, us maintain airbo established, r such as perso Personal prot discussion wi	affinic (CAS 64742-55-8) 1.19 mg/m3 0.74 mg/kg bw/day Value affinic (CAS 64742-55-8) 5.58 mg/m3 0.97 mg/kg bw/day 2.73 mg/m3 Value affinic (CAS 64742-55-8) 9.33 mg/kg ard monitoring procedures. AS 34590-94-8) Can be a l ventilation should be used. the process enclosures, local orne levels below recomment naintain airborne levels to a ornal protective equipment ection equipment should be th the supplier of the person	75 120 Assessment factor 45 72 45 Assessment factor bsorbed through the skin. Ventilation rates should to exhaust ventilation, or ot nded exposure limits. If ex n acceptable level.	Repeated dose toxicity Repeated dose toxicity Notes Repeated dose toxicity Repeated dose toxicity Repeated dose toxicity Notes Oral	

908698 Version #: 02 Revision date: 13-December-2023 Issue date: 12-February-2015

Skin protection	
- Hand protection	Wear appropriate chemical resistant gloves. Wear suitable gloves tested to EN374.
- Other	Wear suitable protective clothing.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Hygiene measures	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

••••• ••• ••• ••• ••• ••• ••• ••• •••	
Appearance	
Physical state	Liquid.
Form	Liquid.
Colour	Blue.
Odour	No data available.
Odour threshold	Not determined.
рН	Material is non soluble in water.
Melting point/freezing point	-39 °C (-38.2 °F)
Initial boiling point and boiling range	Not determined.
Flash point	> 88 °C (> 190.4 °F) Closed cup
Evaporation rate	Not determined.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Explosive limit - lower (%)	Not determined.
Explosive limit – upper (%)	Not determined.
Vapour pressure	Not determined.
Vapour density	Not determined.
Relative density	0.896 (Water = 1)
Solubility(ies)	
Solubility (water)	Insoluble in water.
Partition coefficient (n-octanol/water)	Not applicable, product is a mixture.
Auto-ignition temperature	Not determined.
Decomposition temperature	Not determined.
Viscosity	39 mm²/s (40 °C (104 °F))
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
9.2. Other information	No relevant additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11: Toxicological information

Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of e Inhalation	xposure Prolonged inhalation may be h	armful.	
Skin contact	Prolonged skin contact may cause temporary irritation.		
Eye contact	Direct contact with eyes may cause temporary irritation.		
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.		
Symptoms	Exposure may cause temporary irritation, redness, or discomfort.		
11.1. Information on toxicologic	al effects		
Acute toxicity	Not expected to be acutely tox	ic.	
Components	Species	Test Results	
Dipropylene glycol monomethyl et	•		
<u>Acute</u> Dermal			
LD50	Rabbit	9.5 g/kg	
Distillates (petroleum), hydrotreate	ed light paraffinic (CAS 64742-55		
Acute			
Dermal			
LD50	Rabbit	> 5000 mg/kg, 24 Hours	
Inhalation			
Aerosol LC50	Rat	> 5.53 mg/l, 4 Hours	
Oral	Nat	> 5.55 mg/i, 4 Hours	
LD50	Rat	> 5000 mg/kg	
Hydrocarbons, C11-C14, n-alkane	s, isoalkanes, cyclics, <2% aron		
Acute	, , , , , ,		
Dermal			
LD50	Rabbit	> 5000 mg/kg	
Inhalation			
<i>Vapour</i> LC50	Rat	> 5000 mg/m³, 4 hours	
Oral	Nat	> 5000 mg/m , 4 hours	
LD50	Rat	> 5000 mg/kg	
Skin corrosion/irritation	Due to partial or complete lack	of data the classification is not possible.	
Serious eye damage/eye irritation		of data the classification is not possible.	
Respiratory sensitisation	Due to partial or complete lack	of data the classification is not possible.	
Skin sensitisation	Due to partial or complete lack	of data the classification is not possible.	
Germ cell mutagenicity	Due to partial or complete lack	of data the classification is not possible.	
Carcinogenicity	Due to partial or complete lack	of data the classification is not possible.	
IARC Monographs. Overall	Evaluation of Carcinogenicity		
Highly refined mineral oil Hydrocarbons, C11-C14, <2% aromatics (CAS -)	(CAS -) n-alkanes, isoalkanes, cyclics,	3 Not classifiable as to carcinogenicity to humans. 3 Not classifiable as to carcinogenicity to humans.	
Reproductive toxicity	Due to partial or complete lack	of data the classification is not possible.	
Specific target organ toxicity - single exposure	Due to partial or complete lack	of data the classification is not possible.	
Specific target organ toxicity - repeated exposure	Due to partial or complete lack	of data the classification is not possible.	
Aspiration hazard	Based on available data, the c	lassification criteria are not met.	
Mixture versus substance information	No information available.		
Other information	Prolonged and repeated conta dermatitis and skin cancer.	ct with used oil may cause serious skin diseases, such as	

SECTION 12: Ecological information

I2.1. Toxicity	Based on available data, the classification criteria are not met for hazardous to the aqu environment.			
Components		Species	Test Results	
Dipropylene glycol monomethyl etl	her (CAS 3459	0-94-8)		
Aquatic				
Acute				
Crustacea	LC50	Daphnia magna	1919 mg/l, 48 hours	
Fish	LC50	Pimephales promelas	> 10000 mg/l, 96 hours	
Chronic				
Crustacea	NOAEL	Daphnia magna	0.5 mg/l, 22 days	
Hydrocarbons, C11-C14, n-alkane	s, isoalkanes, o	cyclics, <2% aromatics (CAS -)		
Aquatic				
Acute				
Algae	EL50	Algae	> 1000 mg/l, 72 hours	
Crustacea	LL50	Water flea (Daphnia magna)	> 1000 mg/l, 48 hours	
Fish	LL50	Rainbow trout (Oncorhynchus mykiss)	> 1000 mg/l, 96 hours	
2.2. Persistence and degradability	Expected to I	be inherently biodegradable.		
2.3. Bioaccumulative potential	No data avai	lable.		
Partition coefficient n-octanol/water (log Kow)	Not available			
Bioconcentration factor (BCF)	Not available	Not available.		
2.4. Mobility in soil	No data avai	No data available.		
I2.5. Results of PBT and vPvB assessment	bioaccumula	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.		
2.6. Other adverse effects	No data avai	lable.		

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. - 14.6.: Not regulated as dangerous goods.

RID

14.1. - 14.6.: Not regulated as dangerous goods.

ADN

14.1. - 14.6.: Not regulated as dangerous goods.

ΙΑΤΑ

14.1. - 14.6.: Not regulated as dangerous goods.

IMDG

14.1. - 14.6.: Not regulated as dangerous goods.14.7. Transport in bulkNot established.according to Annex II ofMARPOL 73/78 and the IBCCodeCode

Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Retained direct EU regulations

- Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.
- Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended
 - Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.
- Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Not listed.
- Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

NUL IISLEU.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended - Conditions of restriction given for the associated entry number should be considered

Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations	
	ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.
	ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. CAS: Chemical Abstract Service.
	CEN: European Committee for Standardization.
	IATA: International Air Transport Association.
	IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.
	IMDG: International Maritime Dangerous Goods.
	MARPOL: International Convention for the Prevention of Pollution from Ships.
	PBT: Persistent, bioaccumulative and toxic.
	RID: Regulations concerning the International Carriage of Dangerous Goods by Rail. STEL: Short term exposure limit.
	TWA: Time Weighted Average.
	vPvB: Very persistent and very bioaccumulative.
	LC50: Lethal Concentration, 50%.
	LD50: Lethal Dose, 50%.
	LL50: Lethal level, 50%.
	EL50: Effective level, 50%.
References	Not available.
Information on evaluation method leading to the classification of mixture	The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.
Full text of any statements, which are not written out in full	
under sections 2 to 15	H304 May be fatal if swallowed and enters airways.
	H411 Toxic to aquatic life with long lasting effects.
This SDS contains revisions in the following section(s):	All sections.
Training information	Follow training instructions when handling this material.

Husqvarna AB cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.